

CEL-SPAN®

VCI 720N



Cel-Span® VCI 720N

Vapor corrosion inhibitor additive for film applications.

Cel-Span® VCI 720N is a Vapor Corrosive Inhibitor or anti-corrosion inhibitor concentrated in pellet form in a polyolefins base resin. This product emits a vapor that adheres to the surface of the part and forms a corrosion inhibiting layer protecting metals from corrosion. Cel-Span® VCI 720N is free from nitrates with no adverse effects in use. The direct cost of atmospheric corrosion initiative of oxygen, moisture, and acid type compounds in metals and alloys is estimated at 5 billion annually. The use of VCI (Vapor Corrosive Inhibitors) is one way to protect these metals from corrosion. These VCI products emit a vapor that condenses on the surface of the part and forms a corrosion-inhibiting layer.

Applications: PE Sheet and Film

Melt Flow: 20 LDPE (grams/10min.), at 190 C

Blend Density: 0.945g/cc

Types of Resins: PE

Amount Required: 4% - 6% (depending on thickness of film)

Features and Benefits:

- Meets Military specifications PRF-22019E
- Multi Metal formulation
- RoHS compliant
- No Nitrates

Cel-Span® VCI 720N is heat sealable with standard equipment. However, bags or sheets can be tied, folded, taped, or stapled for protection equivalent to heat sealable enclosure. The VCI film does not have to be in contact with the metal to protect, the vapors that travel to all portions of the enclosure. Anti-corrosion properties are activated immediately after the production of the film. VCI films exhibit anti-corrosion properties at temperatures below 5°C/41°F. Optimum protection effect is best when objects are completely sealed within the film. This product is free from nitrates with no adverse health effects from the use of this product are known. All additives in the formulation are GRAS & TOSCA approved. Cel-Span® VCI 720N is packaged in 220 lb. polyethylene lined fiber drums. We recommend that this product be kept closed in its original container and in a dry place.

Disclaimer - This data contains general Information and describes typical properties only. Only persons qualified to determine for themselves the suitability of our products for particular purposes should evaluate its potential uses. No guarantee is made or liability assumed, the application of this data and the products describes herein being at the sole risk of the user. Samples are provided to the requestor on an "AS IS, WHERE IS" evaluation purpose only basis, solely under the use and direction of the requestor, without warranty of any kind (either express or implied), including but not limited to any implied warranties of merchantability and fitness for a specific or general purpose and those arising by statute or by law, or from a cause of dealing or usage of trade. In no event, regardless of cause, shall AxiPolymer be liable for any indirect, special, incidental, punitive or consequential damages of any kind, whether arising under breach of contract, tort (including negligence), strict liability or otherwise, and whether based on this agreement or otherwise, even if advised of the possibility of such damages.