

CEL-SPAN®



Process Enhancer 606C

Cel-Span® Process Enhancer 606C

A coupling, compatilizing and processing concentrate for polycarbonate applications.

Cel-Span® Process Enhancer 606C in a polycarbonate resin carrier used in extrusion and injection processes to compatibilize dissimilar resins into polycarbonate, couple additives and enhance flow and reduce the processing temperature and increase productivity for all polycarbonate resins. Cel-Span® Process Enhancer 606C contains a unique additive that enhances the flow characteristics of polycarbonate resins in injection molding processes, reducing the cycle time while improving mold filling in multiple cavity molds. In compounding, extrusion, blow molding applications, Cel-Span® Process Enhancer 606C also couples additives such as minerals, fiberglass, and flame retardants to polycarbonate resins, while increasing distribution. Compatibilization of dissimilar resins, which might have contaminated resin streams, can be manufactured into more homogeneous matrices at lower percentages without the use of acid type of compatibilizers, which could increase decomposition of various resins. The reduction in processing and melt temperatures results in less polymer degradation, better color, lower cycle time and higher output especially in injection, blow molding and sheet applications. This product has no effect on the high clarity performance of most polycarbonate resins.

Applications: Injection - Compounding - Extrusion - Blow Molding

Recommended usage level: 1.0% to 2.0%.

Since the carrier resin for Cel-Span® Process Enhancer 606C is polycarbonate, we recommend drying which is typical when using polycarbonate resins.

For injection molding processes, adjust machine conditions so that the work energy is maintained in the screw. We also recommend that the rear zone temperatures be reduced by 15 – 20% and the front zone by 5 – 10%.

Cel-Span® Process Enhancer 606C additives are listed on the TASCA list. There are no adverse health effects from the use of Cel-Span® Process Enhancer 606C. Cel-Span® Process Enhancer 606C is packaged in 55 lb. plastic bags or 1,100 lb. gaylord boxes. We recommend this product be kept closed and stored in the original container, away from light, heat and highly humid environments.

Disclaimer - This data contains general Information and describes typical properties only. Only persons qualified to determine for themselves the suitability of our products for particular purposes should evaluate its potential uses. No guarantee is made or liability assumed, the application of this data and the products describes herein being at the sole risk of the user. Samples are provided to the requestor on an "AS IS, WHERE IS" evaluation purpose only basis, solely under the use and direction of the requestor, without warranty of any kind (either express or implied), including but not limited to any implied warranties of merchantability and fitness for a specific or general purpose and those arising by statute or by law, or from a cause of dealing or usage of trade. In no event, regardless of cause, shall AxiPolymer be liable for any indirect, special, incidental, punitive or consequential damages of any kind, whether arising under breach of contract, tort (including negligence), strict liability or otherwise, and whether based on this agreement or otherwise, even if advised of the possibility of such damages.