

CEL-SPAN®



Purge 300HT

Cel-Span® Purge 300HT

Cel-Span® Purge 300HT contains several proprietary additives that are essential in the purging process of high temperature resins and was created to be the least cost prohibitive high temperature purge compound on the market today. Cel-Span® Purge 300HT can be used directly without any mixing necessary to clean most plastic equipment during color, and resin changes. The unique additives in Cel-Span® Purge 300HT, makes it possible to purge colors and degradation in less time than other purging compounds

Applications: Injection Molding – Pipe/Profile

Temperature Range: 550°F – 750°F (288°C – 400°C)

Types of Resins: PEEK, UHMW-HDPE, PEEK,PPS, PEK and PES

Amount Required: 1 – 3 times barrel capacities suggested, but actual amount depends on machine conditions

Features and Benefits:

- Easy to use
- No process changes needed
- Use at the normal resin processing temperature and RPM speed
- Safe, non-hazardous materials with FDA compliance
- No mixing required
- One year shelf life
- Not just a mechanical purge

Cel-Span® Purge 300HT can be used directly without any mixing necessary to clean most plastics equipment during color, and resin changes. The unique additives and resin system in Cel-Span® Purge 300HT, make it possible to purge color resins in less time, in most resin applications. Cel-Span® Purge 300HT is packaged in 55 lb. plastic bags and in 1,100 gaylord boxes. We recommend this product be kept closed and stored in the original container, away from light, heat, and highly humid environments.

Disclaimer - This data contains general Information and describes typical properties only. Only persons qualified to determine for themselves the suitability of our products for particular purposes should evaluate its potential uses. No guarantee is made or liability assumed, the application of this data and the products describes herein being at the sole risk of the user. Samples are provided to the requestor on an "AS IS, WHERE IS" evaluation purpose only basis, solely under the use and direction of the requestor, without warranty of any kind (either express or implied), including but not limited to any implied warranties of merchantability and fitness for a specific or general purpose and those arising by statute or by law, or from a cause of dealing or usage of trade. In no event, regardless of cause, shall AxiPolymer be liable for any indirect, special, incidental, punitive or consequential damages of any kind, whether arising under breach of contract, tort (including negligence), strict liability or otherwise, and whether based on this agreement or otherwise, even if advised of the possibility of such damages.